

FA Series

Drying Ovens Fan Forced



- Ideal for drying and sterilization with reduced processing time
- Temperature range 5°C above ambient to 250°C
- Outer body - steel coated in epoxy and resistant paint
- Internal chamber - stainless steel AISI 304 with rounded corners
- Electronic temperature control by PID microprocessor and PT 100 probe
- One ramp function, timer
- Visual alarm "over-temp" thermostat
- Adjustable ventilation by means of rear exhaust duct diam.50 mm



Model	Capacity Litres	Precision	Chamber WxDxH mm	Overall WxDxH mm	Self position	Shelf Code	Power Watts.	Voltage VAC.	Weight Kg.
FA.10.030	30 L	+/- 2°C at 150°C	300x340x360	520x600x570	5	101002	1000	240	35
FA.10.060	60 L	+/- 2°C at 150°C	380x350x450	600x660x680	7	101003	1200	240	50
FA.10.080	80 L	+/- 2°C at 150°C	400x400x500	620x710x730	7	101003	1200	240	50
FA.10.125	125 L	+/- 2°C at 150°C	500x500x500	720x810x730	9	101004	2000	240	60
FA.10.150	150 L	+/- 2°C at 150°C	500x500x600	720x810x830	10	101005	2000	240	75
FA.10.240*	240 L	+/- 3°C at 150°C	600x500x800	820x840x1030	12	101006	3000	240	100
FA.10.430**	430 L	+/- 3°C at 150°C	600x600x1200	820x940x1430	14	101007	3000	240	165
FA.10.720	720 L	+/- 3°C at 150°C	700x700x1470	920x1040x1750	20	101008	5400	415 3P.	200
FA.10.1000***	1000 L	+/- 3°C at 150°C	1000x700x1470	1250x1040x1750	20	101009	5400	415 3P.	250

*FA. 10.240 available with 10 amp plug

**FA. 10.430 available with 10 amp plug

***FA. 10.1000 Double doors