

Microbiological Incubators

MI Series Microbiological Incubators

- Suitable for most accurate and reproducible temperature controlled applications.
- Temperature range 5°C above ambient to 100°C.
- Steel outer body coated in corrosive resistant epoxy paint.
- Stainless steel AISI 304 Internal chamber with rounded corners.
- Inner glass door.
- Natural convection.
- Electronic temperature controlled by PID microprocessor and PT100 probe.
- Visual alarm “over-temp” thermostat and manual reset.
- Fibreglass thermal insulation.
- Two stainless steel wire shelves included.
- Three stainless steel wire shelves included for 430L, 720L and 1000L cabinets.



Model	Capacity Litres	Precision	Internal W x D x H mm	External W x D x H mm	Shelf Positions	Shelf Code	Power Watts	Volt- age VAC	Weight Kg
MI.10.030	30L	+/- 0.5°C at 37°C	300 x 340 x 360	520 x 600 x 570	5	10.1002	250	240	35
MI.10.060	60L	+/- 0.5°C at 37°C	380 x 350 x 450	600 x 660 x 680	7	10.1003	300	240	50
MI.10.125	125L	+/- 0.5°C at 37°C	500 x 500 x 500	720 x 810 x 730	9	10.1004	500	240	60
MI.10.150	150L	+/- 0.5°C at 37°C	500 x 500 x 600	720 x 810 x 830	10	10.1005	500	240	75
MI.10.240	240L	+/- 0.5°C at 37°C	600 x 500 x 800	820 x 840 x 1030	12	10.1006	750	240	100
MI.10.430	430L	+/- 0.5°C at 37°C	600 x 600 x 1200	820 x 940 x 1430	14	10.1007	1100	240	165
MI.10.720	720L	+/- 0.5°C at 37°C	700 x 700 x 1470	920 x 1040 x 1750	20	10.1008	1100	240	200
MI.10.1000*	1000L	+/- 0.5°C at 37°C	1000 x 700 x 1470	1250 x 1040 x 1750	20	10.1009	1500	240	250

*Double Doors

Electronic Timer (10.1100)

Options / Accessories:

- Access Port
- Door with window and interior lighting