

Glassware Drying Ovens

GD Series

Glassware Drying Oven

- Electronic temperature control by PID microprocessor and PT100 probe.
- Temperature range 5°C above ambient to 120°C.
- Fan forced – on/off.
- Toughened glass door (safety glass).
- Powder coated steel exterior.
- Stainless steel interior.
- Adjustable shelf position.
- Cabinet supplied with a sliding stainless steel shutter on the top for ventilation.
- Two stainless steel wire shelves included.
- Three stainless steel wire shelves included for the 500L and 1000L cabinets.



Model	Capacity Litres	Precision	Internal W x D x H mm	External W x D x H mm	Shelf Positions	Shelf Code	Power Watts	Voltage VAC	Weight Kg
GD.10.125	125L	+/- 3°C at 70°C	500 x 500 x 500	620 x 600 x 700	4	10.1004	1000	240	20
GD.10.250	250L	+/- 3°C at 70°C	600 x 500 x 800	720 x 600 x 1000	4	10.1006	1500	240	20
GD.10.500	500L	+/- 3°C at 70°C	600 x 500 x 1600	720 x 600 x 1750	4	10.1007	2000	240	20
GD.10.1000*	1000L	+/- 3°C at 70°C	1000 x 700 x 1600	1120 x 800 x 1750	4	10.1009	2400	240	20

*Double Doors