

EC Series— Refrigerated incubators



Precision Refrigerated Incubators are available in different sizes with cooling and heating ranging from 5° C to 60° C. Competitively priced, these incubators are suitable for applications such as general microbiological incubating.

- Large LCD colours touch screen display controls for temperature with time-segment programming.
- SD memory card support, pattern and graft can be download
- Temperature range: 5°C to +60°C, fluctationn +/- 0.1°C
- Access port with silicone plug diam.50mm.
- 3 stainless steel shelf (self reinforced on request)
- LED shelf cassette (optional)

Model	Capacity	Chamber W x D x H mm	Overall W x D x H mm	Shelf position	Shelf code	Power Watts.	Voltage VAC.	Weight Kg.
EC 80	80 L	400x400x500	720x710x1100	6	10.1015	1000	240	100
EC150	150 L	500x500x600	720x810x1200	10	10.1005	1200	240	125
EC 240	240 L	600x500x800	820x840x1400	12	10.1006	1500	240	170
EC 430	430 L	600x600x1200	820x940x1800	14	10.1007	2000	240	220
EC 720	720 L	700x700x1470	920x1040x2050	20	10.1008	2400	240	300
EC 1000*	1000 L	1000x700x1470	1250x1040x2050	20	10.1009	3500	240	500

*ECCG 1000 with double door

LED shelf cassette option

Know-how

- Customized solution and dimensions that you need .
- Customized integration of accessories.
- Customized connections, access ports.

MADE IN AUSTRALIA

